

MF GC1700 Series Specifications

Model:	MF GC1705 Tractor	MF GC1715 Tractor	MF GC1720 Tractor Loader-Backhoe
Engine			
Engine Power HP	22.5	24.5	24.5
PTO hp	18.7	19.6	19.6
Rated engine speed	2,600	3,000	3,000
Type	3-cylinder diesel	3-cylinder diesel	3-cylinder diesel
Displacement: in³ (cc)	68.5 (1,123)	68.5 (1,123)	68.5 (1,123)
Cooling system	Liquid-cooled	Liquid-cooled	Liquid-cooled
Fuel tank capacity (L)	25	25	25
Transmission			
Control	Dual foot pedal	Dual foot pedal	Dual foot pedal
Hydrostatic	2 range w/cruise	2 range w/cruise	2 range w/cruise
Forward speeds: km/h (mph)	0-14.7 (0-9.1)	0-14.7 (0-9.1)	0-14.7 (0-9.1)
Rear brakes	Wet disc	Wet disc	Wet disc
Rear PTO			
Rear PTO kW (HP)	13.9 (18.7)	14.6 (19.6)	14.6 (19.6)
Type	Independent	Independent	Independent
Speed	540 @ 2,532	540 @ 2,829	540 @ 2,829
Shaft	Fixed	Fixed	Fixed
Configuration	6 spline	6 spline	6 spline
Mid PTO			
Type	Independent	Independent	Independent
Speed	2,000 @ 2,476	2,000 @ 2,947	2,000 @ 2,947
Configuration	15 spline	15 spline	15 spline
Hydraulics			
Type of system	Open centre	Open centre	Open centre
Total flow: L/min (gpm)	24.0 (6.3)	26.3 (6.8)	26.3 (6.8)
Factory joystick	Standard	Standard	Standard
3-Point Hitch			
ASAE hitch	Cat. I	Cat. I	Cat. I
Rate of drop control	Standard	Standard	Standard
Lift capacity @ hitch point: kg (lbs)	540 (1,190)	540 (1,190)	540 (1,190)
Type of stabilisers	Turnbuckle	Turnbuckle	Turnbuckle
Type of link ends	Fixed	Fixed	Fixed
Operator Area			
Platform-ROPS	Fixed	Fixed	Fixed
Seat type	Coil spring	Coil spring	Reversable
Seat belt type	Retractable	Retractable	Retractable
Hood type	Flip-up	Flip-up	Flip-up
Dimensions With Turf Tyres			
Overall length: mm (in)	2,480 (97.6)	2,480 (97.6)	4,496 (177)
Max width @ rear combo light: mm (in)	1,200 (47.25)	1,200 (47.25)	1,370 (53.9)
Maximum height over ROPS: mm (in)	1,850 (72.8)	1,850 (72.8)	2,185 (86)
Ground clearance: mm (in)	170 (6.7)	170 (6.7)	170 (6.7)
Wheelbase: mm (in)	1,450 (57.1)	1,450 (57.1)	1,450 (57.1)
Shipping weight: kg (lbs)	650 (1,433)	650 (1,433)	1,221 (2670)

Implement Specifications

Deck Model:	GC2300
Type	
60" mid-mount	Drive-over rotary deck
General	
Discharge type	Side
Number of blades	3 (overlapping)
Gearbox drive	Shaft
Speed	2,000 rpm
Blade tip speed	18,856 rpm
Gauge wheels	4
Scalp rollers	3
Raise & lower actuation	Via 3 point linkage
Height control	Manual adjustment
Transport height	150 mm
Dimensions (mm)/Weight (kg)	
Cutting width	1,524 mm
Overall width	1,900 mm
Weight	200 kg
Overall height	524 mm
Capacities	
Gearbox	800 cc



facebook.com/MasseyFergusonGlobal
 twitter.com/AGCOcorp
 youtube.com/MasseyFergusonVideo
 blog: agccorp.com

Every effort has been made to ensure that the information contained in this publication is as accurate and current as possible. However, inaccuracies, errors or omissions may occur and details of the specifications may be changed at any time without notice. Therefore, all specifications should be confirmed with your Massey Ferguson Dealer or Distributor prior to any purchase.

Backhoe Model	CB65
Max digging depth m (in)	1.97 (77.5)
Max reach m (in)	2.73 (107.5)
Transport height m (in)	1.8 (70.9)
Stabiliser Spread (Transport) m (in)	1.2 (47)
Stabiliser Spread (Operating) m (in)	2.04 (80.3)
Loading height m (in)	1.68 (66)
Angle of departure (deg)	20
Swing Arc (deg)	150
Bucket Rotation (deg)	177
Shipping weight kg (lbs)	288 (635)
Digging Force (Bucket) kg (lbs)	1,123 (2,476)
Digging Force (Dipper) kg (lbs)	793 (1,748)



22.5-24.5 HP
MF GC1700
 Compact Tractors. Big Performance.



Massey Ferguson GC Series Compact Tractors

The versatile all-rounder – perfect for any job



Axles

► Robust front and rear axles to handle a wide range of accessories and front end loaders.

Quality mowing decks

► 60 inch side discharge deck available for residential or commercial use.
► Drive over deck.

Dual hydrostatic control pedals

► Control pedals allow forward and reverse control for maximum comfort.

Differential lock

► The differential lock can be easily engaged using the foot pedal. Combined with 4WD, it ensures consistent and reliable traction through tough and slippery conditions.

Cruise control

► Newly designed cruise control.
► Improves driving comfort.
► Can result in better fuel efficiency.



Compact size with BIG tractor performance

For both residential and professional operations, the MF GC1700 Series delivers across the board performance – from easier operation and greater comfort to reducing fatigue, improving safety and maximising productivity. The MF GC1700 Series tractors are designed to make light work of big jobs. Yet, their compact size and versatile handling mean they're ideal for hobby farmers, landscapers, homeowners and residential contractors.

With engines ranging up to 24.5 hp and unmatched versatility, the MF GC1700 is easy to drive, and can handle everything from mowing, loading, general farm work and more. So if your workload demands a real tractor, check out the MF GC1700 Series. It delivers on every job, every time.



Engine features

- 3-cylinder liquid cooled engine.
- Solid metal hood with tilt design and open/close handle for easy access to serviceable areas.
- Radiator with removable mesh screen to shield radiator from debris and allow access for cleaning.
- 1.123 litre engine providing high torque at lower RPM.



Operator's area

- Ergonomic seat, designed to custom fit all profiles.
- Uncluttered platform to ensure ample room for movement.
- Hydraulic joystick located on right side of console, for easy access.
- Safety lock-out lever prevents accidental joystick movement.
- Cruise control engagement through push lever located on dashboard.



Tyres

- Turf, Ag or Industrial options are available to best suit the tasks at hand.



Three point linkage

- A large three point linkage lift capacity of 540 kg.



Loader

- Australian made standard or 4-in-1 loader available.



Construction

- The heavy-duty sub-frame design keeps durability and serviceability in mind with welded booms featuring a hard-wearing, powder coat finish, connected by locking, galvanised pins that become an integral part of the backhoe frame.



Easy mounting and removal

- Make full use of the three point linkage without removing the backhoe sub-frame with a four-point mounting system and quick-attach design. The self-standing backhoe can also be easily removed.

Boom float

- The boom float makes it much easier for the operator to position the bucket, create an even floor bed in the cut and provide smooth grading operation when backfilling. Achieve increased operator comfort and productivity from faster digging speeds and cycle times, while reducing overall fuel consumption.